

# **RVON-I/O**

# Stand-Alone 8-Port RVON Adapter for Matrices & Keypanels

Coupled with the same VoIP technology used with the RVON-8, the RVON-I/O takes analog audio and converts it to digital VoIP audio. By being able, to convert analog audio systems to digital VoIP audio the RVON-I/O expands the boundaries of digital audio to include analog. There are many applications in which the RVON-I/O can be used, such as:

- The conversion from analog to VoIP digital audio (and vice versa)
- Zeus Matrix to RVON-I/O to RVON- 1, or RVON-8, RVON-I/O to standard analog keypanel
- Zeus to RVON-I/O to RVON-1
- RVON-8 to RVON-I/O to Zeus to a keypanel.

RVON-I/O is fully compatible with following internationally recognized standards and protocols: G.711, G.729A and B, and G.723.

# **Features**

### Installation

The RVON-I/O provides a single RJ-45 Ethernet connection for use with a 10 BASE-T or 100 BASE-TX network.

### 8 Channels of Audio In and Out

The RVON-I/O supports with 8 channels IN and OUT and has configurable network and bandwidth parameters that can be tailored to individual network functions.

### **Trunk Capable**

The RVON-I/O supports ancillary data control for use with RTS Intelligent Trunking.


### Addressing


Eight individually addressable audio channels. The RVON-I/O can feed simultaneously VoIP (voice over internet protocol) capable keypanels as well as various other matrix intercom systems.

## **Ethernet Compatible**

The RVON-I/O uses standard Ethernet protocols and is compatible with 10 BASE-T and 100 BASE-TX Ethernet compliant devices and networks

# Line Drawing





# **RVON-I/O Specifications**

# **Digital**

Compression	Audio Bit Rate	Coding Delay	Playout Delay	IP Bandwidth
G.711	64k	125µs	20-60ms	160-224 kbps
G.729 A & B	8k	10ms	20-120ms	32-112 kbps
G.723	5.3k/6.3k	30ms	60-120ms	29-45 kbps

## **Connections**

**RJ-45 Ethernet** 

DB-9 Serial port (8 AIO channels)

**DB-25 Serial Port** 


DB-9 Relay Port

### **Power**

90-240 VAC

# **Physical Dimensions**

1.72" H (44mm) 19" (482.6 mm) W X 8" (203.2 mm) D



### **Contact Information**

Telex Communications, Inc. 12000 Portland Avenue South Burnsville, Minnesota 55337 Telephone: 877-863-4169 Fax: 800-955-6831

Form Number: 38110-403

Date: April, 2006

# **Ordering Information**

# **RVON-I/O**

Stand-alone 8-port RVON adapter for matrices & keypanels

Catalog Number: 90007772000

This specifications information is preliminary and is subject to change without notification.

Brand names mentioned are the property of their respective companies.